

BONDERITE**BONDERITE C-AK 5975 A AERO**Known as TURCO 5975 A
October 2013**PRODUCT DESCRIPTION**

BONDERITE C-AK 5975 A AERO provides the following product characteristics:

Technology	Metal Cleaning
Product Type	Alkaline Cleaner
Application	Sprayable

BONDERITE C-AK 5975 A AERO is an amber liquid formulated to remove heavy soils, such as greases, oils and road dirt from engines, chassis, tracks, transmission and differentials by pressure spray methods. BONDERITE C-AK 5975 A AERO may be foamed onto vertical and overhead surfaces and can be used on ferrous and nonferrous alloys. BONDERITE C-AK 5975 A AERO should not be sprayed onto electrical equipment. BONDERITE C-AK 5975 A AERO meets the requirements of MIL-C-43616 C.

Application Areas

BONDERITE C-AK 5975 A AERO offers these features:

1. Free of phenols, chromate and chlorinated hydrocarbons.
2. Concentrate has flash point of 63°C, Tag Closed Cup method.
3. Readily mixes with tap water at recommended concentrations.
4. Readily mixes from parts and equipment with high-pressure water or air/water rinser.
5. Used at ambient temperature, no heat required.

TECHNICAL DATA

Appearance	clear liquid
pH-value	9.5 to 9.9
Density, g/ml	0.993 to 1.003

DIRECTION OF USE**Preliminary Statement**

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

Use instructions**Equipment:**

Tank, spray gun and associated equipment may be fabricated from mild steel or stainless steel.

Mixing:

Add BONDERITE C-AK 5975 A AERO at 20% by volume to tap water and mix thoroughly.

Applications:

Apply water/BONDERITE C-AK 5975 A AERO solution by means of a non-atomizing spray or by conventional foamers. Allow sufficient time for solution to work. Rinse with high-pressure cold water or air/water rinser. Steam may also be used to rinse heavily soiled equipment.

Note:

BONDERITE C-AK 5975 A AERO can be applied between 5° to 45°C. Optimum temperatures have been found to be from 20° to 30° C.

Storage

Temperature, °C	0 to 40
Shelf-life (in unopened original packaging), months	24

Classification

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazardous Information
Transport Regulations
Safety Regulations



ADDITIONAL INFORMATION

Disclaimer

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0