

# **BONDERITE C-MC 1495 X**

Known as TURCO 1495-X September 2013

### **PRODUCT DESCRIPTION**

BONDERITE C-MC 1495 X provides the following product characteristics:

Technology	Metal Pretreatment
Product Type	Polish and cleaner
Application	Manual

BONDERITE C-MC 1495 X is a medium-heavy duty aircraft polish and cleaner. It quickly removes oxide films and corrosion products from aircraft surfaces-cleans and polishes aircraft to a high luster.

#### **Application Areas**

BONDERITE C-MC 1495 X offers these features:

1. For use on all aircraft metals

2. Especially effective for cleaning and polishing alclad aluminum

3. Excellent for use on painted surfaces to remove exhaust deposits and oxidized paint

4. Can be used on high strength steel; will not cause hydrogen embrittlement

5. Very high lubricating properties facilitate polishing and protect metals, whether used as a hand

polish or with a power buffer

6. Will not leave swirl or scratch marks associated with power buffing

### **TECHNICAL DATA**

Appearancewhite viscousViscosity (20° C, 30 rpm), mPa.s4,000 to 5,000

## **DIRECTION OF USE**

#### **Preliminary Statement**

Prior to use it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

### **Use instructions**

Before applying the BONDERITE C-MC 1495 X polish, it is advisable to wash the aircraft to remove heavy soil, oil and exhaust deposits.

BONDERITE C-MC 1495 X is furnished in a viscous liquid form, ready to use. Apply sparingly with a piece of toweling or small paintbrush. Polish with power buffer or by hand, using clean, soft toweling or cloths.

Change polishing head or cloths frequently the oxides and film removed by the BONDERITE C-MC 1495 X will load-up and adversely affect the efficiency of the BONDERITE C-MC 1495 X polish and its results.

#### Storage

Temperature, °C0 to 50Shelf-life (in unopened original packaging),24months24

### Classification

Please refer to the corresponding **Material Safety Data Sheets** for details on:

Hazardous Information Transport Regulations Safety Regulations



#### ADDITIONAL INFORMATION Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

# In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

# In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits. The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. <sup>®</sup> denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0